

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

Serial No. 09/960,020

In the specification:

Please amend the paragraph beginning on page 5, line 27 as follows:

FIGS. 4 and 5 illustrate a rivet 66 for use with the instrument 10. The rivet 66 comprises a round head 68 from which extends axially 3 leaves 70. A cylindrical plug 72 extends axially from the head 68 in the opposite direction and is ~~frangible~~ frangibly connected to the head 68 through a frangible connection 74. The surfaces of the leaves 70 are curved so that the combination of the three leaves 70 provides an overall tubular configuration. Application of force in the axial direction applied to the plug 72 breaks its frangible connection 74 with the head 68 and allows it to drive axially into a position between the leaves 70 thus causing the leaves 70 to spread.